

EARTHMAX SR 46 - Spécifications techniques



Description

Earthmax SR 46 pour tombereaux rigides apporte une réponse novatrice aux milieux rocheux, abrasifs et hostiles des mines. Ce pneu a été particulièrement conçu pour le transport de charges lourdes et il offre une résistance exceptionnelle aux coupures et déchirures et permet donc un cycle de vie plus long du produit. La carcasse et les ceintures All Steel (Tout Acier) assurent une protection extraordinaire contre les coups, sollicitations et crevaisons afin de maximiser les heures de travail et donc augmenter la productivité. Earthmax SR 46 est caractérisé par un dessin spécial de la bande de roulement qui est dotée de crampons à blocs avec rainurage le long de la circonférence. Ceci confère donc d'excellentes performances dans les virages avec un minimum de dommages sur la partie externe de la bande de roulement.

UM

US Standard

Construction

 RADIAL

Machinery

OTR: Tombereau rigide

Version	HEAT RESISTANT COMPOUND
Type	TL
Tyre Size	27.00 R 49
LI/SS	223 B

Dimensions US Standard

Usa code	94055159
TMPH	449
Overall Width (inch)	29.4
Overall Diameter (inch)	105.8
Static Loaded Radius (inch)	48.2
Rolling Circumference (inch)	321.5
Rim Rec	19.50/4.0
Rim Alt	-
Star Rating	**
TRA Code	E4

Load capacity (lbs)

mph / psi	73	76	80	83	87	91	94	98	102
30	45400	48100	49400	50700	52000	55100	56800	58400	60000

Printed on 04/05/2024 16:13

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..