

## EARTHMAX SR 51 - Spécifications techniques



### Description

EARTHMAX SR 51 (L-5) est un pneu radial **All Steel** (Tout Acier) particulièrement conçu pour les chargeuses et bulldozers. EARTHMAX SR 51 est idéal pour les opérations pénibles qui exigent une plus grande résistance aux coupures, une protection des flancs et une traction exceptionnelle.

### UM

International Standard

### Construction

 RADIAL

### Machinery

OTR: Bulldozer • Chargeur

|           |                        |
|-----------|------------------------|
| Version   | CUT RESISTANT COMPOUND |
| Type      | TL                     |
| Tyre Size | 29.5 R 29              |
| LI/SS     | 211 A2                 |

## Dimensions International Standard

|                            |                      |
|----------------------------|----------------------|
| Overall Width (mm)         | 777                  |
| Overall Diameter (mm)      | 1990                 |
| Static Loaded Radius (mm)  | 842                  |
| Rolling Circumference (mm) | 5872                 |
| Rim Rec                    | 25.00/3.5            |
| Rim Alt                    | 24.00/3.5, 26.00/3.5 |
| Star Rating                | *                    |
| TRA Code                   | L5                   |

## Load capacity (Kg)

| km/h / bar | 4.00  | 4.25  | 4.5   | 4.75  | 5.00  |
|------------|-------|-------|-------|-------|-------|
| 10         | 16500 | 17000 | 18000 | 18500 | 19500 |

Printed on 03/05/2024 03:17

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..