

## AGRIMAX ELOS - Technical Specifications



### Description

AGRIMAX ELOS has been designed to enhance top traction performance even under particularly awkward operating conditions on wet terrains such as paddy fields or marshland. The tread design has been especially developed to ensure optimum self-cleaning properties, which are essential for operations on muddy land and during transfers. To optimize the farmers' productivity reducing machine downtime, sidewall protectors have been integrated into the design of the AGRIMAX ELOS tire to ensure maximum protection against possible damages at any time.

### UM

US Standard

### Construction

 RADIAL

### Machinery

Agriculture: Tractor

Version	STANDARD
Type	TL
Tyre Size	520/85 R 42 (20.8 R 42)
LI/SS	167A8/B

## Dimensions US Standard

Usa code	94075850
Section Width (inch)	20.3
Overall Diameter (inch)	78.3
Static Loaded Radius (inch)	36.2
Rolling Circumference (inch)	240
Rim Rec	DW 16 L
Rim Alt	DD 18 L ; DW 18 L
ECE	E11-106R-0010146
TRA Code	R2

## Load capacity (lbs)

mph / psi	14	17	20	23	29	35	41	46	52	58
30	4700	5530	6370	7100	7940	8650	9500	10460	11300	12010
25	4700	5530	6370	7100	7940	8650	9500	10460	11300	12010
20	5030	5920	6820	7590	8500	9270	10160	11200	12090	12860
5 LT	6280	7420	8540	9500	10640	11600	12730	14020	15140	16100
5 HT	5030	5920	6820	7590	8500	9270	10160	11200	12090	12860

Printed on 12/05/2024 22:11

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..