

AGRIMAX V-FLECTO - Technical Specifications



Description

AGRIMAX V-FLECTO is BKT's response to the challenging demand of both technology and performance for high-power tractors. This tire is perfect for soil tillage and haulage applications thanks to reduced soil compaction and self-cleaning properties. With the exclusive VF technology, AGRIMAX V-FLECTO can carry heavy loads with a lower inflating pressure compared to standard and IF tires, reaching high speeds. It also features the Narrow Rim Option that allows mounting standard rims on the tire. BKT has designed this tire with optimized geometry to enhance driving comfort both in the fields and on the road reducing fuel consumption.

UM

International Standard

Construction

 RADIAL

Machinery

Agriculture: High-Power Tractor

Version	STANDARD
Type	TL
Tyre Size	VF 650/60 R 34
LI/SS	168 D

Dimensions International Standard

Section Width (mm)	660
Overall Diameter (mm)	1676
Static Loaded Radius (mm)	750
Rolling Circumference (mm)	4996
SRI (mm)	775
Rim Rec	DW 23 B
Rim Alt	DW21B
ECE	E11-106R-007210

Load capacity (Kg)

km/h / bar	0.6	0.8	1.0	1.2	1.4	1.6	2.0
70	2605	3010	3420	3880	4235	4590	5100
From 65 to 40	2860	3305	3755	4260	4650	5040	5600
30	2915	3375	3830	4345	4745	5145	5715
20	2975	3375	3830	4345	4745	5145	5715
10	3145	3635	4130	4685	5115	5545	6160
*Upto 10 Cyc with front loader	4000	4630	5255	5960	6510	7060	7840
10 HT	2915	3375	3830	4345	4745	5145	5715

* *For Upto 10 Cyc with front loader application inflation pressure to be increased by 0.8 bar.

Printed on 03/05/2024 18:06

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..