

AGRIMAX V-FLECTO - Technical Specifications



Description

AGRIMAX V-FLECTO is BKT's response to the challenging demand of both technology and performance for high-power tractors. This tire is perfect for soil tillage and haulage applications thanks to reduced soil compaction and self-cleaning properties. With the exclusive VF technology, AGRIMAX V-FLECTO can carry heavy loads with a lower inflating pressure compared to standard and IF tires, reaching high speeds. It also features the Narrow Rim Option that allows mounting standard rims on the tire. BKT has designed this tire with optimized geometry to enhance driving comfort both in the fields and on the road reducing fuel consumption.

UM

US Standard

Construction

 RADIAL

Machinery

Agriculture: High-Power Tractor

Version	STANDARD
Type	TL
Tyre Size	VF 650/60 R 38 NRO
LI/SS	173 D

Dimensions US Standard

Usa code	94065370
Section Width (inch)	25.6
Overall Diameter (inch)	68.7
Static Loaded Radius (inch)	30.5
Rolling Circumference (inch)	205.4
Rim Rec	DW 23 B
Rim Alt	DW 21 B
Narrow Rim option	DW 20 B
ECE	E11-106R-006415
TRA Code	R1W

Load capacity (lbs)

mph / psi	9	12	15	17	20	23	29	35
45	6010	6910	7960	8870	9920	10820	12140	13040
From 40 to 25	6590	7590	8740	9740	10890	11890	13330	14330
20	6720	7750	8920	9940	11110	12140	13600	14620
12	6860	7900	9090	10140	11330	12380	13870	14900
5	7250	8360	9620	10720	11980	13080	14660	15760
*Upto 5 Cyc with front loader	9240	10640	12250	13650	15260	16650	18660	20060
5 HT	6720	7750	8920	9940	11110	12140	13600	14620

* *For Upto 10 Cyc with front loader application inflation pressure to be increased by 0.8 bar.

Printed on 03/05/2024 21:48

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..