

AGRIMAX V-FLECTO - Technical Specifications



Description

AGRIMAX V-FLECTO is BKT's response to the challenging demand of both technology and performance for high-power tractors. This tire is perfect for soil tillage and haulage applications thanks to reduced soil compaction and self-cleaning properties. With the exclusive VF technology, AGRIMAX V-FLECTO can carry heavy loads with a lower inflating pressure compared to standard and IF tires, reaching high speeds. It also features the Narrow Rim Option that allows mounting standard rims on the tire. BKT has designed this tire with optimized geometry to enhance driving comfort both in the fields and on the road reducing fuel consumption.

UM

US Standard

Construction

 RADIAL

Machinery

Agriculture: High-Power Tractor

Version	STANDARD
Type	TL
Tyre Size	VF650/65 R 34 NRO
LI/SS	170 D

Dimensions US Standard

Usa code	94074778
Section Width (inch)	25.6
Overall Diameter (inch)	67.3
Static Loaded Radius (inch)	30
Rolling Circumference (inch)	202.9
Rim Rec	DW 23 B
Rim Alt	DW 21 B
Narrow Rim option	DW 20 B
ECE	E11-106R-008812
TRA Code	R1W

Load capacity (lbs)

mph / psi	9	12	15	17	20	23	29
45	6130	7100	8060	9140	9990	10950	12040
From 40 to 25	6750	7800	8860	10050	10980	12300	13230
20	6880	7960	9040	10250	11190	12540	13490
12	7010	8110	9210	10450	11410	12790	13760
5	7420	8580	9740	11060	12070	13520	14550
*Upto 5 Cyc with front loader	9440	10920	12400	14060	15370	17220	18520
5 HT	6880	7960	9040	10250	11190	12540	13490

* *For Upto 10 Cyc with front loader application inflation pressure to be increased by 0.8 bar.

Printed on 03/05/2024 20:18

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..