

# AGRIMAX V-FLECTO - Technical Specifications



## Description

AGRIMAX V-FLECTO is BKT's response to the challenging demand of both technology and performance for high-power tractors. This tire is perfect for soil tillage and haulage applications thanks to reduced soil compaction and self-cleaning properties. With the exclusive VF technology, AGRIMAX V-FLECTO can carry heavy loads with a lower inflating pressure compared to standard and IF tires, reaching high speeds. It also features the Narrow Rim Option that allows mounting standard rims on the tire. BKT has designed this tire with optimized geometry to enhance driving comfort both in the fields and on the road reducing fuel consumption.

## UM

International Standard

## Construction

 RADIAL

## Machinery

Agriculture: High-Power Tractor

Version	STANDARD
Type	TL
Tyre Size	VF900/60 R 38 NRO
LI/SS	187 D

## Dimensions International Standard

Section Width (mm)	881
Overall Diameter (mm)	2045
Static Loaded Radius (mm)	882
Rolling Circumference (mm)	6053
SRI (mm)	975
Rim Rec	DW 30 B
Narrow Rim option	DW 27 B
ECE	E11-106R-009004
TRA Code	R1W

## Load capacity (Kg)

km/h / bar	0.6	0.8	1.0	1.2	1.4	1.6	2.0
70	4345	5055	5855	6565	7275	7985	8870
From 65 to 40	4775	5555	6435	7215	7995	8775	9750
30	4870	5665	6560	7355	8150	8950	9945
20	4965	5775	6690	7500	8310	9125	10140
10	5250	6110	7075	7935	8790	9650	10725
*Upto 10 Cyc with front loader	6685	7775	9005	10100	11190	12285	13650
10 HT	4870	5665	6560	7355	8150	8950	9945

\* \*For Upto 10 Cyc with front loader application inflation pressure to be increased by 0.8 bar.

Printed on 03/05/2024 19:34

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..