# AGRIMAX FORCE - Specifiche tecniche

## Description

AGRIMAX FORCE, il prodotto di punta di BKT, è uno pneumatico radiale appositamente progettato per la lavorazione del terreno e le applicazioni di trasporto e raccolta con trattori e mietitrici ad alta potenza, garantendo massime prestazioni ed efficienza. Grazie alla tecnologia IF, questo pneumatico è in grado di trasportare carichi pesanti con una pressione di gonfiaggio inferiore rispetto a uno pneumatico standard riducendo la compattazione del suolo. AGRIMAX FORCE è caratterizzato da un tallone rinforzato e offre eccellente trazione, ottime proprietà di autopulitura e consumi ridotti oltre ad un'esperienza di guida confortevole.

## UM

US Standard

## Construction

RADIAL

## Machinery

Agricoltura: Mietitrebbia • Trattore a elevata potenza

| | |
|---|---|
| **Version** | STANDARD |
| **Type** | TL |
| **Tyre Size** | IF 710/60 R 34 CFO |
| **LI/SS** | 170 D |

## Dimensions US Standard

| | |
|---|---|
| **Usa code** | 94022229 |
| **Section Width (inch)** | 27.9 |
| **Overall Diameter (inch)** | 67.6 |
| **Static Loaded Radius (inch)** | 30 |
| **Rolling Circumference (inch)** | 201.8 |
| **Rim Rec** | DW 25 B |
| **ECE** | E4-106R-001485 |
| **TRA Code** | R1W |

## Load capacity (lbs)

| mph / psi | 9 | 12 | 15 | 17 | 20 | 23 | 29 | 35 |
|---|---|---|---|---|---|---|---|---|
| **45** | 5530 | 6370 | 7340 | 8180 | 9140 | 9990 | 11190 | 12040 |
| **from 40 to 25** | 6080 | 7010 | 8070 | 8990 | 10050 | 10980 | 12300 | 13200 |
| **20** | 6330 | 7290 | 8390 | 9350 | 10450 | 11410 | 12790 | 13760 |
| **12** | 6570 | 7560 | 8710 | 9710 | 10850 | 11850 | 13280 | 14290 |
| **5** | 7730 | 8900 | 10240 | 11420 | 12760 | 13930 | 15620 | 16800 |
| **Upto 20 Cyc** | 7900 | 9100 | 10480 | 11680 | 13060 | 14260 | 15980 | 17200 |
| **Upto 10 Cyc** | 9420 | 10860 | 12500 | 13930 | 15570 | 17010 | 19060 | 20500 |
| **Upto 5 Cyc** | 10340 | 11920 | 13710 | 15290 | 17080 | 18660 | 20910 | 22490 |
| **5 HT** | 6330 | 7290 | 8390 | 9350 | 10450 | 11410 | 12790 | 13760 |

Printed on 05/05/2024 21:52

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..