

AGRIMAX RT 765M - Specifiche tecniche



Description

AGRIMAX RT 765M, uno pneumatico della serie 70 di BKT, è ideale per equipaggiare i trattori più moderni impegnati in applicazioni pesanti, quali lavorazioni del terreno, spostamenti su campo e su strada, la vendemmia e irrorazioni. L'ampia area di contatto garantisce la migliore trazione e ottimo comfort su tutte le superfici in qualsiasi momento. Questo pneumatico offre elevate proprietà di autopulitura e assicura una compattazione del suolo ridotta. Sono disponibili due misure dotate di tecnologia con cinture in acciaio.

UM

International Standard

Construction

 RADIAL

Machinery

Agricoltura: Macchina irroratrice • Trattore • Vendemmiatrice

Version	SPECIAL
Type	TL
Tyre Size	710/70 R 42
LI/SS	176 D/179 A8

Dimensions International Standard

Section Width (mm)	716
Overall Diameter (mm)	2061
Static Loaded Radius (mm)	922
Rolling Circumference (mm)	6174
SRI (mm)	975
Rim Rec	DW 23 B
Rim Alt	DW 25 B
ECE	E11-106R-006001
TRA Code	R1W

Load capacity (Kg)

km/h / bar	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4	2.8
65	3055	3550	4050	4545	5045	5540	6110	6465	7100
50	3210	3730	4250	4775	5295	5815	6415	6785	7455
40	3335	3875	4420	4960	5505	6045	6665	7055	7750
30	3515	4085	4655	5230	5800	6370	7025	7435	8165
10 LT	4095	4760	5425	6090	6760	7425	8185	8660	9515
10 HT	3515	4085	4655	5230	5800	6370	7025	7435	8165

Printed on 03/05/2024 08:16

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..