

AW 09 - Specifiche tecniche



Description

AW 09 è stato sviluppato per lavorazioni del terreno, la raccolta del fieno e applicazioni di trasporto con attrezzi agricoli, presse per balle di fieno e rimorchi. È idoneo per essere impiegato nell'agricoltura moderna sia su strada che fuori strada. La carcassa rinforzata garantisce un'elevata capacità di carico nonché un ciclo di vita prolungato dello pneumatico. AW 09 è stato sviluppato con una particolare miscela resistente a tagli e lacerazioni che garantisce una straordinaria resistenza alle stoppie.

UM

International Standard

Construction

❖ BIAS

Machinery

Agricoltura: Pressa per balle di fieno • Mietitrebbia •
Attrezzi agricoli • Rimorchio

Version	STANDARD
Type	TL
Tyre Size	300/80 - 15.3
LI/SS DRIVE WHEEL	129 A8
LI/SS FREE ROLLING	141 A8

Dimensions International Standard

Section Width (mm)	295
Overall Diameter (mm)	860
Static Loaded Radius (mm)	376
Rolling Circumference (mm)	2520
Rim Rec	9.00
ECE	E4-106R-000376

Load capacity (Kg)

	km/h / bar	4.00
	10 FR	3605
	25 FR	3065
	30 FR	2885
	40 FR	2575
	10 DW	2590
	25 DW	2200
	30 DW	2070
	40 DW	1850

Printed on 30/04/2024 19:46

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..