

AW 09 - Specifiche tecniche



Description

AW 09 è stato sviluppato per lavorazioni del terreno, la raccolta del fieno e applicazioni di trasporto con attrezzi agricoli, presse per balle di fieno e rimorchi. È idoneo per essere impiegato nell'agricoltura moderna sia su strada che fuori strada. La carcassa rinforzata garantisce un'elevata capacità di carico nonché un ciclo di vita prolungato dello pneumatico. AW 09 è stato sviluppato con una particolare miscela resistente a tagli e lacerazioni che garantisce una straordinaria resistenza alle stoppie.

UM

International Standard

Construction

❖ BIAS

Machinery

Agricoltura: Pressa per balle di fieno • Mietitrebbia •
Attrezzi agricoli • Rimorchio

Version	STANDARD
Type	TL
Tyre Size	320/80 - 15.3
LI/SS DRIVE WHEEL	133 A8
LI/SS FREE ROLLING	145 A8

Dimensions International Standard

Section Width (mm)	309
Overall Diameter (mm)	901
Static Loaded Radius (mm)	392
Rolling Circumference (mm)	2640
Rim Rec	9.00
ECE	E4-106R-000378

Load capacity (Kg)

	km/h / bar	4.00
	10 FR	4060
	25 FR	3450
	30 FR	3250
	40 FR	2900
	10 DW	2885
	25 DW	2450
	30 DW	2305
	40 DW	2060

Printed on 30/04/2024 12:46

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..