

## EARTHMAX SR 30 - Specifiche tecniche



### Description

EARTHMAX SR 30 (E-3/L-3) è uno pneumatico radiale All Steel progettato per il duplice impiego con loader o dumper articolati. Le cinture d'acciaio multistrato e il disegno rigido a blocchi assicurano trazione, stabilità e durabilità eccellenti. La speciale mescola resistente al taglio rende EARTHMAX SR 30 la soluzione ideale per una varietà di condizioni operative dure.

### UM

International Standard

### Construction

 RADIAL

### Machinery

OTR: Dumper articolato • Dozer • Pala caricatrice

Version	CUT RESISTANT COMPOUND
Type	TL
Tyre Size	20.5 R 25
LI/SS	193 A2

## Dimensions International Standard

Overall Width (mm)	529
Overall Diameter (mm)	1487
Static Loaded Radius (mm)	663
Rolling Circumference (mm)	4439
Rim Rec	17.00/2.0
Rim Alt	17.00/1.7
Star Rating	**
TRA Code	L3

## Load capacity (Kg)

km/h / bar	5.25	5.50	5.75	6.00	6.25	6.50
10	9750	10000	10300	10900	11200	11500

Printed on 01/05/2024 12:50

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..