

EARTHMAX SR 30 - Specifiche tecniche



Description

EARTHMAX SR 30 (E-3/L-3) è uno pneumatico radiale All Steel progettato per il duplice impiego con loader o dumper articolati. Le cinture d'acciaio multistrato e il disegno rigido a blocchi assicurano trazione, stabilità e durabilità eccellenti. La speciale miscela resistente al taglio rende EARTHMAX SR 30 la soluzione ideale per una varietà di condizioni operative dure.

UM

US Standard

Construction

 RADIAL

Machinery

OTR: Dumper articolato • Dozer • Pala caricatrice

Version	CUT RESISTANT COMPOUND
Type	TL
Tyre Size	29.5 R 25
LI/SS	208 A2

Dimensions US Standard

Usa code	94054466
Overall Width (inch)	30.1
Overall Diameter (inch)	73.3
Static Loaded Radius (inch)	32.2
Rolling Circumference (inch)	218.7
Rim Rec	25.00/3.5
Star Rating	*
TRA Code	L3

Load capacity (lbs)

mph / psi	58	62	65	69	73
5	34200	35300	37500	38600	39700

Printed on 02/05/2024 01:05

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..