

EARTHMAX SR 53 - Specifiche tecniche



Description

EARTHMAX SR 53 è uno pneumatico radiale All Steel particolarmente progettato per loader, dozer e dumper di basso profilo (LPDT) che operano in condizioni difficili negli ambienti rocciosi, incluse le operazioni in miniere sotterranee e nei cantieri di demolizione. Il battistrada profondo L-5 e la miscela resistente ai tagli garantiscono una vita prolungata dello pneumatico nonché trazione e stabilità ottime.

UM

International Standard

Construction

 RADIAL

Machinery

OTR: Dozer • Pala caricatrice • Dumper di basso profilo

Version	CUT RESISTANT COMPOUND (UMS)
Type	TL
Tyre Size	26.5 R 25

Dimensions International Standard

Overall Width (mm)	680
Overall Diameter (mm)	1788
Static Loaded Radius (mm)	800
Rolling Circumference (mm)	5376
Rim Rec	22.00/3.0
Star Rating	**
TRA Code	L5

Load capacity (Kg)

* "Consult BKT representative for load and pressure details."

Printed on 16/04/2024 23:30

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..