

## EARTHMAX SR 53 - Specifiche tecniche



### Description

EARTHMAX SR 53 è uno pneumatico radiale All Steel particolarmente progettato per loader, dozer e dumper di basso profilo (LPDT) che operano in condizioni difficili negli ambienti rocciosi, incluse le operazioni in miniere sotterranee e nei cantieri di demolizione. Il battistrada profondo L-5 e la miscela resistente ai tagli garantiscono una vita prolungata dello pneumatico nonché trazione e stabilità ottime.

### UM

US Standard

### Construction

 RADIAL

### Machinery

OTR: Dozer • Pala caricatrice • Dumper di basso profilo

|           |                        |
|-----------|------------------------|
| Version   | CUT RESISTANT COMPOUND |
| Type      | TL                     |
| Tyre Size | 45/65 R 45             |
| LI/SS     | 245 A2                 |

## Dimensions US Standard

|                              |           |
|------------------------------|-----------|
| Usa code                     | 94053575  |
| Overall Width (inch)         | 44.3      |
| Overall Diameter (inch)      | 107.5     |
| Static Loaded Radius (inch)  | 47.7      |
| Rolling Circumference (inch) | 323.8     |
| Rim Rec                      | 36.00/4.5 |
| Star Rating                  | **        |
| TRA Code                     | L5        |

## Load capacity (lbs)

| mph / psi | 76    | 80    | 83     | 87     | 91     | 94     |
|-----------|-------|-------|--------|--------|--------|--------|
| 5         | 96500 | 99000 | 102000 | 104500 | 110000 | 113500 |

Printed on 16/04/2024 23:20

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..