

## EARTHMAX SR 55 - Specifiche tecniche



### Description

EARTHMAX SR 55 è uno pneumatico radiale All Steel specialmente progettato per loader, dozer e pale LHD che operano nelle condizioni più severe come nelle cave e miniere, nonché nei cantieri di demolizione. Grazie al disegno del battistrada extra profondo e liscio EARTHMAX SR 55 è in grado di raggiungere elevati picchi di produttività con minori tempi di fermo macchina, assicurando ottima durabilità. Gli operatori delle macchine apprezzeranno anche stabilità e trazione straordinarie.

### UM

International Standard

### Construction

 RADIAL

### Machinery

OTR: Dozer • Pala LHD • Pala caricatrice

|           |                        |
|-----------|------------------------|
| Version   | CUT RESISTANT COMPOUND |
| Type      | TL                     |
| Tyre Size | 35/65 R 33             |
| LI/SS     | 224 A2                 |

## Dimensions International Standard

|                            |           |
|----------------------------|-----------|
| Overall Width (mm)         | 900       |
| Overall Diameter (mm)      | 2065      |
| Static Loaded Radius (mm)  | 915       |
| Rolling Circumference (mm) | 6175      |
| Rim Rec                    | 28.00/3.5 |
| Rim Alt                    | --        |
| Star Rating                | **        |
| TRA Code                   | L5S       |

## Load capacity (Kg)

| km/h / bar | 5.25  | 5.50  | 5.75  | 6.00  | 6.25  | 6.50  |
|------------|-------|-------|-------|-------|-------|-------|
| 10         | 23600 | 25000 | 25750 | 26500 | 27250 | 28000 |

Printed on 27/04/2024 04:55

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..