

## F 240 - Specifiche tecniche



### Description

F 240 è uno pneumatico forestale particolarmente sviluppato per la movimentazione dei tronchi. Il disegno del battistrada assicura eccellente trazione, ottime proprietà di autopulitura oltre a buona manovrabilità. La mescola superiore del battistrada garantisce straordinaria resistenza a tagli e usura per una lunga vita operativa dello pneumatico. F 240 è caratterizzato da una larga area di contatto che si traduce in migliore stabilità.

### UM

US Standard

### Construction

 BIAS

### Machinery

Agricoltura: Macchina a straccio

Version	STANDARD
Type	TT
Tyre Size	400 - 15.5 (400 - 15.5)

## Dimensions US Standard

Usa code	94051588
Ply Rating	12
Section Width (inch)	15.9
Overall Diameter (inch)	34.1
Rim Rec	AG 13.00
ECE	E11-106R-004260
TRA Code	LS2

## Load capacity (lbs)

mph / psi	55
20	6945

Printed on 07/05/2024 03:56

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..