

FARM 2000 - Specifiche tecniche



Description

Lo pneumatico FARM 2000 è idoneo per trattori nelle applicazioni per la lavorazione del suolo. È stato realizzato con una miscela speciale resistente a tagli e lacerazioni che assicura una durabilità migliore. Grazie alla carcassa robusta, FARM 2000 offre elevata capacità di carico nonché trazione e proprietà di autopulitura eccellenti.

UM

US Standard

Construction

 BIAS

Machinery

Agricoltura: Trattore

Version	STANDARD
Type	TT
Tyre Size	250/80 - 18
LI/SS DRIVE WHEEL	115 A8
LI/SS FREE ROLLING	127 A8

Dimensions US Standard

Usa code	94040285
Section Width (inch)	9.4
Overall Diameter (inch)	34.3
Static Loaded Radius (inch)	15.5
Rolling Circumference (inch)	105.5
Rim Rec	W 8
Rim Alt	W7 ; W9
ECE	E11-106R-003519
TRA Code	R1

Load capacity (lbs)

	mph / psi	41
	5 FR	5400
	15 FR	4600
	20 FR	4320
	25 FR	3860
	5 DW	3750
	15 DW	3190
	20 DW	3000
	25 DW	2680

Printed on 14/05/2024 18:37

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..