

## FARM 2000 - Specifiche tecniche



### Description

Lo pneumatico FARM 2000 è idoneo per trattori nelle applicazioni per la lavorazione del suolo. È stato realizzato con una miscela speciale resistente a tagli e lacerazioni che assicura una durabilità migliore. Grazie alla carcassa robusta, FARM 2000 offre elevata capacità di carico nonché trazione e proprietà di autopulitura eccellenti.

### UM

US Standard

### Construction

 BIAS

### Machinery

Agricoltura: Trattore

|                    |               |
|--------------------|---------------|
| Version            | STANDARD      |
| Type               | TL            |
| Tyre Size          | 300/80 - 15.3 |
| LI/SS DRIVE WHEEL  | 120 A8        |
| LI/SS FREE ROLLING | 132 A8        |

## Dimensions US Standard

|                              |                 |
|------------------------------|-----------------|
| Usa code                     | 94034673        |
| Section Width (inch)         | 11.8            |
| Overall Diameter (inch)      | 35              |
| Static Loaded Radius (inch)  | 15.3            |
| Rolling Circumference (inch) | 102.7           |
| Rim Rec                      | 9.00            |
| ECE                          | E11-106R-003517 |

## Load capacity (lbs)

| mph / psi | 41   |
|-----------|------|
| 5 FR      | 6170 |
| 15 FR     | 5250 |
| 20 FR     | 4940 |
| 25 FR     | 4410 |
| 5 DW      | 4320 |
| 15 DW     | 3670 |
| 20 DW     | 3460 |
| 25 DW     | 3090 |

Printed on 14/05/2024 20:43

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..