

## FARM 2000 - Specifiche tecniche



### Description

Lo pneumatico FARM 2000 è idoneo per trattori nelle applicazioni per la lavorazione del suolo. È stato realizzato con una miscela speciale resistente a tagli e lacerazioni che assicura una durabilità migliore. Grazie alla carcassa robusta, FARM 2000 offre elevata capacità di carico nonché trazione e proprietà di autopulitura eccellenti.

### UM

International Standard

### Construction

 BIAS

### Machinery

Agricoltura: Trattore

Version	STANDARD
Type	TT
Tyre Size	8.3 - 24
LI/SS	105 A6

## Dimensions International Standard

Ply Rating	8
Section Width (mm)	211
Overall Diameter (mm)	995
Static Loaded Radius (mm)	473
Rolling Circumference (mm)	3032
Rim Rec	W 7
Rim Alt	W 6
ECE	E11-106R-004094
TRA Code	R1

## Load capacity (Kg)

km/h / bar	3.10
30	925

Printed on 14/05/2024 21:43

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..