

FARM 2000 - Scheda tecnica



Description

Lo pneumatico FARM 2000 è idoneo per trattori nelle applicazioni per la lavorazione del suolo. È stato realizzato con una miscela speciale resistente a tagli e lacerazioni che assicura una durabilità migliore. Grazie alla carcassa robusta, FARM 2000 offre elevata capacità di carico nonché trazione e proprietà di autopulitura eccellenti.

UM

International Standard

Construction

 BIAS

Machinery

Agricoltura: Trattore

SIZE	Version	TRA Code	LI/SS	LI/SS DRIVE WHEEL	LI/SS FREE ROLLING	PR	RIM REC	RIM ALT	SW	OD	SLR	RC	SRI	Type	ECE
260/70 - 15.3	STANDARD			114 A8	126 A8		9.00		265	775	349	2294	360	TL	E11-106R-003516
300/80 - 15.3	STANDARD			120 A8	132 A8		9.00		300	890	388	2608	410	TL	E11-106R-003517
250/80 - 16	STANDARD	R1		113 A8	125 A8		W 8	W 7 ; W 9 ; W 8 L	240	820	369	2429	390	TT	E11-106R-003518
250/80 - 16	STANDARD	R1		113 A8	125 A8		W 8	W 7 ; W 9 ; W 8 L	240	820	369	2429	390	TL	E11-106R-003518
250/80 - 18	STANDARD	R1		115 A8	127 A8		W 8	W 7 ; W 9	240	870	394	2679	410	TT	E11-106R-003519
250/80 - 18	STANDARD	R1		115 A8	127 A8		W 8	W 7 ; W 9	240	870	394	2679	410	TL	E11-106R-003519
8 - 18	STANDARD	R1	85 A6			4	W 6		195	840	390	2458		TT	E11-106R-004084
8 - 18	STANDARD	R1	94 A6			6	W 6		195	840	393	2539		TT	E11-106R-002960
8.3 - 20	STANDARD	R1				4	W 7		210	895	431	2714		TT	E11-106R-004369
8.3 - 20	STANDARD	R1				6	W 7		210	895	431	2714		TT	E11-106R-002957
8.3 - 24	STANDARD	R1				6	W 7	W 6	211	995	473	3032		TT	
8.3 - 24	STANDARD	R1	105 A6			8	W 7	W 6	211	995	473	3032		TT	E11-106R-004094
12.4 - 28	STANDARD	R1	123 A6			8	W 11	W 9 ; W 10	320	1288	603	3969	600	TT	
12.4 - 28	STANDARD	R1	124 A6			10	W 11	W 9 ; W 10	320	1288	603	3969	600	TT	E11-106R-005964
12.4 - 28	STANDARD	R1	125 A6			12	W 11	W 9 ; W 10	320	1288	603	3969	600	TT	E11-106R-005965
13.6 - 28	SPECIAL	R1	128 A6			12	W 12	W 11	345	1335	622	4080	625	TT	E11-106R-003002
13.6 - 28	STANDARD	R1	128 A6			12	W 12	W 11	345	1335	622	4080	625	TT	E11-106R-003002
13.6 - 28	STANDARD	R1	125 A6			8	W 12	W 11	345	1335	622	4080	625	TT	E11-106R-004373
13.6 - 28	STANDARD	R1	127 A6			10	W 12	W 11	345	1335	622	4080	625	TT	E11-106R-004374
14.9 - 28	STANDARD	R1	134 A6			12	W 13	W 11 ; W 12	385	1375	636	4194	650	TT	E11-106R-005966
14.9 - 28	STANDARD	R1	136 A6			14	W 13	W 11 ; W 12	385	1375	636	4194	650	TT	E11-106R-005968
14.9 - 28	STANDARD	R1	130 A6			8	W 13	W 11 ; W 12	385	1375	636	4194	650	TT	E11-106R-004375
14.9 - 28	STANDARD	R1	132 A6			10	W 13	W 11 ; W 12	385	1375	636	4194	650	TT	E11-106R-005967

16.9 - 28	HD	R1	135 A6	8	W 15 L	W 14 L	429	1420	657	4351	675	TT	E11- 106R- 004378
16.9 - 28	STANDARD	R1	143 A6	12	W 15 L	W 14 L	429	1420	657	4351	675	TT	E11- 106R- 003627
18.4 - 30	STANDARD	R1	151 A6	14	W 16 L		470	1560	716	4776		TT	E11- 106R- 004525

Printed on 14/05/2024 23:38

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..