RIDEMAX FL 693 M - Specifiche tecniche

Description

RIDEMAX FL 693 M è lo pneumatico ideale per chi deve percorrere frequentemente tratti stradali con rimorchi/autobotti. Sviluppato per un utilizzo del 75% su strada, RIDEMAX FL 693 M mostra delle prestazioni eccellenti su strada, dando la priorità al comfort e alle proprietà di autopulitura. L'indice di velocità classe D/E della gamma è sinonimo di velocità più elevate sui percorsi stradali con significativo risparmio di tempo. La bassa resistenza al rotolamento contribuisce ad un consumo minore di carburante, mentre il tallone rinforzato e le cinture in acciaio garantiscono una durabilità superiore.

UM

International Standard

Construction

RADIAL

Machinery

Agricoltura: Autobotte • Rimorchio

Version	STANDARD
Type	TL
Tyre Size	710/50 R 26.5
LI/SS	170 D

Dimensions International Standard

Section Width (mm)	727
Overall Diameter (mm)	1383
Static Loaded Radius (mm)	624
Rolling Circumference (mm)	4217
SRI (mm)	650
Rim Rec	AG 24.00
Rim Alt	AG 20.00
ECE	E4-106R-001422

Load capacity (Kg)

km/h / bar	1.0	1.2	1.6	2.0	2.4	2.8	3.2	3.6	4.0
70	2020	2290	2780	3220	3710	4200	4525	5015	5450
65	2220	2520	3060	3540	4080	4620	4980	5520	6000
50	2690	3050	3705	4285	4940	5595	6030	6680	7260
40	3025	3430	4165	4815	5550	6285	6775	7510	8160
25	3510	3985	4835	5595	6450	7300	7870	8725	9480
10	4000	4540	5510	6375	7345	8320	8965	9940	10800

Printed on 05/05/2024 01:54

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..