

## TR 459 - Specifiche tecniche



### Description

TR 459 è stato specificamente progettato per operazioni di scavo e di carico nonché applicazioni nel settore municipalità e manutenzione con trattori e terne. Lo pneumatico offre elevata stabilità ed è disponibile in due versioni. La versione "special" garantisce un ciclo di vita prolungato dello pneumatico.

### UM

International Standard

### Construction

 BIAS

### Machinery

Agricoltura: Terna • Trattore  
Industriale: Terna

Version	INDUSTRIAL
Type	TL
Tyre Size	17.5L - 24
LI/SS	144 A8

## Dimensions International Standard

Ply Rating	10
Section Width (mm)	445
Overall Diameter (mm)	1270
Static Loaded Radius (mm)	557
Rolling Circumference (mm)	3825
Rim Rec	DW 15 L
Rim Alt	DW 14 L
ECE	E11-106R-005285
TRA Code	R4

## Load capacity (Kg)

km/h / bar	2.20
40	2800

Printed on 15/05/2024 10:18

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..