

## AW 702 - Especificações técnicas



### Description

AW 702 foi desenvolvido para implementos agrícolas, reboques e compressores de palha nas aplicações para trabalhar a terra e para o transporte. Este pneu para operações pesadas foi projetado pela BKT para proporcionar um novo nível de duração. AW 702 está disponível em versões diferentes para responder às exigências específicas dos utilizadores: uma versão "aramid belted" com cintos em aramida, que fornece uma maior resistência às perfurações, uma versão "HD" com um composto resistente aos cortes e lacerações, enquanto a versão "special" fornece uma resistência aos restolhos.

### UM

International Standard

### Construction

 BIAS

### Machinery

Agricultura: Enfardadeira de feno • Implementos agrícolas

• Reboque

Industrial: Reboque

|                    |              |
|--------------------|--------------|
| Version            | STANDARD     |
| Type               | TT           |
| Tyre Size          | 14.5/80 - 18 |
| LI/SS FREE ROLLING | 155 A8       |

## Dimensions International Standard

|                            |                 |
|----------------------------|-----------------|
| Ply Rating                 | 12              |
| Section Width (mm)         | 374             |
| Overall Diameter (mm)      | 1047            |
| Static Loaded Radius (mm)  | 446             |
| Rolling Circumference (mm) | 3068            |
| Rim Rec                    | 11.0            |
| Rim Alt                    | 12 ; 13         |
| ECE                        | E11-106R-003601 |

## Load capacity (Kg)

| km/h / bar | 3.40 |
|------------|------|
| 10 FR      | 4550 |
| 25 FR      | 3870 |
| 30 FR      | 3640 |
| 40 FR      | 3250 |

Printed on 28/04/2024 19:42

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..