

AW 729 - Especificações técnicas



Description

O AW 729 é um pneu agrícola concebido especificamente para aplicações de transporte, colheita de feno, enfardamento e lavoura. O formato arredondado e três ranhuras centrais no piso proporcionam baixa compactação do solo e evitam danos no campo. O AW 729 é o pneu ideal para a agricultura moderna e é adequado tanto para uso dentro como fora da estrada.

UM

International Standard

Construction

 BIAS

Machinery

Agricultura: Enfardadeira de feno • Implementos agrícolas
• Reboque

| | |
|--------------------|-------------|
| Version | STANDARD |
| Type | TL |
| Tyre Size | 380/55 - 17 |
| LI/SS DRIVE WHEEL | 122 A8 |
| LI/SS FREE ROLLING | 134 A8 |

Dimensions International Standard

| | |
|----------------------------|-----------------|
| Ply Rating | 10 |
| Section Width (mm) | 385 |
| Overall Diameter (mm) | 850 |
| Static Loaded Radius (mm) | 377 |
| Rolling Circumference (mm) | 2560 |
| Rim Rec | 13.00 |
| Rim Alt | 13 ; W 13 |
| ECE | E11-106R-008727 |

Load capacity (Kg)

| km/h / bar | 2.60 |
|------------|------|
| 10 FR | 2970 |
| 25 FR | 2520 |
| 30 FR | 2375 |
| 40 FR | 2120 |
| 10 DW | 2100 |
| 25 DW | 1785 |
| 30 DW | 1680 |
| 40 DW | 1500 |

Printed on 17/05/2024 14:22

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..