

## FLOTATION 648 T - Dados técnicos



### Description

FLOTATION 648 T é especialmente idóneo para aplicações de colheita de feno e de transportes no campo e na estrada. O desenho do piso particular permite transportar cargas muito elevadas com pressões baixas, garantindo propriedades excepcionais de autolimpeza. O pneu é também sinonimo de tração e durabilidade excelentes.

### UM

International Standard

### Construction

 BIAS

### Machinery

Agricultura: Ceifeira

SIZE	Version	LI/SS DRIVE WHEEL	LI/SS FREE ROLLING	PR	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	ECE
550/45 - 22.5	STANDARD	154 A8/150 B	166 A8/162 B	20	AG 16.00		550	1070	475	3203	TL	E4-106R-002046
550/45 - 22.5	STANDARD	147 A8/144 B	159 A8/156 B	16	AG 16.00		550	1070	475	3203	TL	

Printed on 07/05/2024 15:57

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..