

TF 8181 - Especificações técnicas



Description

TF 8181 é um pneu a ser utilizado no campo e na estrada, desenvolvido para tratores 2WD/2RM nas aplicações para trabalhar o terreno e para o transporte. Este pneu assegura um excelente comando de direção.

UM

International Standard

Construction

 BIAS

Machinery

Agricultura: Trator 2WD

Industrial: Reboque

Version	STANDARD
Type	TT
Tyre Size	10.00 - 16
LI/SS	115 A6

Dimensions International Standard

Ply Rating	8
Section Width (mm)	273
Overall Diameter (mm)	895
Static Loaded Radius (mm)	411
Rolling Circumference (mm)	2667
Rim Rec	W 8
Rim Alt	W 8 L
ECE	E4-106R-002672
TRA Code	F2

Load capacity (Kg)

km/h / bar	2.80
30	1215

Printed on 29/04/2024 11:09

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..