

FS 216 - Specificații tehnice



Descriere

FS 216 are un design robust, cu unghi optim și lățime mai mare pentru a îmbunătăți performanța de tracțiune pentru mașini de tăiat lemne și troliuri de corhănit. Oferă o rezistență excelentă la tăiere și așchiere în cele mai critice condiții de funcționare și asigură o protecție maximă împotriva eventualelor daune în orice moment.

UM

Standard internațional

Construcție

 BIAS

Mașinării

Agricultură: Troliu de corhănit

Versiune	STEEL BELTED
Tip	TL
Dimensiunea anvelopei	DH 35.5L - 32

Dimensiuni Standard internațional

Rating de sarcină	20
Lățimea secțiunii (mm)	907
Overall Diameter (mm)	2011
Static Loaded Radius (mm)	912
Rolling Circumference (mm)	5992
Rim Rec	DH 31
Rim Alt	DH 31 H
ECE	E11-106R-003349
TRA Code	LS2

Load capacity (Kg)

km/h / bar	1.70	2.10
10	-	10200
30	7300	-

Imprimat pe 5/8/2024 4:31 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..