

LG 306 - Specificații tehnice



Descriere

LG 306 este o anvelopă pentru gazon și grădină potrivită pentru mașini de tuns iarba. La unele dimensiuni, LG 306 este potrivită și pentru tractoare mici. Modelul specific al benzii de rulare face ca anvelopa să fie blândă cu solul, facilitând totodată manevrabilitatea. LG 306 este disponibilă într-o versiune cu "bandă din aramidă" pentru utilizatorii care au nevoie de o rezistență sporită la perforare.

UM

US Standard

Construcție

 BIAS

Mașinării

Agricultură: Cositoare • Tractor mic

| | |
|-----------------------|----------------|
| Versiune | STANDARD |
| Tip | TL |
| Dimensiunea anvelopei | 23 X 8.50 - 12 |

Dimensiuni US Standard

| | |
|------------------------------|-------------------------------|
| Usa code | 94012589 |
| Rating de sarcină | 4 |
| Lățimea secțiunii (inch) | 8.3 |
| Overall Diameter (inch) | 22.6 |
| Static Loaded Radius (inch) | 10.2 |
| Rolling Circumference (inch) | 67.3 |
| Rim Rec | 7.00 I - 55 ; I - 70 ; I - 90 |
| Rim Alt | 7 JA |
| ECE | E11-106R-003457 |

Load capacity (lbs)

| | |
|-----------|------|
| mph / psi | 22 |
| 10 | 1100 |

Imprimat pe 5/8/2024 4:50 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..