

TF 9393 - Технические спецификации



Description

TF 9393 — это передние сельскохозяйственные шины, специально разработанные для небольших тракторов, которые используются для обработки почвы и особенно подходят для рыхлого грунта. Протектор шины имеет широкую центральную часть и боковые ребра. Специальный рисунок протектора обеспечивает превосходные характеристики шин на любых поверхностях.

UM

US Standard

Construction

 BIAS

Machinery

Сельское хозяйство: Мини-трактор

Version	STANDARD
Type	TT
Tyre Size	7.50 - 16
LI/SS	103 A6

Dimensions US Standard

Usa code	94046263
Ply Rating	8
Section Width (inch)	8.3
Overall Diameter (inch)	31.9
Rim Rec	5.50 F
Rim Alt	5.00 F ; 6.00 F
TRA Code	F2

Load capacity (lbs)

mph / psi	56
25	1545

Printed on 21.05.2024 0:50

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..