

AGRIMAX ELOS - Tekniska specifikationer



Description

AGRIMAX ELOS har utmärkt dragkraft även under särskilt svåra förhållanden i blöt terräng, till exempel på risfält och i sumpmarker. Däckets slitbanemönster är utvecklat för att ge optimala självrensande egenskaper, vilket är nödvändigt vid användning på lerig mark och vid förflyttningar. Jordbrukarnas produktivitet har optimerats genom att minska stilleståndstiden. Detta uppnås genom att sidoväggsskydd har integrerats i designen för att ge AGRIMAX ELOS maximalt skydd mot alla typer av skador.

UM

US Standard

Construction

 RADIAL

Machinery

Lantbruk: Traktor

| | |
|-----------|----------------------------|
| Version | STANDARD |
| Type | TL |
| Tyre Size | 520/85 R 42 (20.8 R 42) |
| LI/SS | 167A8/B |

Dimensions US Standard

| | |
|------------------------------|-------------------|
| Usa code | 94075850 |
| Section Width (inch) | 20.3 |
| Overall Diameter (inch) | 78.3 |
| Static Loaded Radius (inch) | 36.2 |
| Rolling Circumference (inch) | 240 |
| Rim Rec | DW 16 L |
| Rim Alt | DD 18 L ; DW 18 L |
| ECE | E11-106R-0010146 |
| TRA Code | R2 |

Load capacity (lbs)

| mph / psi | 14 | 17 | 20 | 23 | 29 | 35 | 41 | 46 | 52 | 58 |
|-----------|------|------|------|------|-------|-------|-------|-------|-------|-------|
| 30 | 4700 | 5530 | 6370 | 7100 | 7940 | 8650 | 9500 | 10460 | 11300 | 12010 |
| 25 | 4700 | 5530 | 6370 | 7100 | 7940 | 8650 | 9500 | 10460 | 11300 | 12010 |
| 20 | 5030 | 5920 | 6820 | 7590 | 8500 | 9270 | 10160 | 11200 | 12090 | 12860 |
| 5 LT | 6280 | 7420 | 8540 | 9500 | 10640 | 11600 | 12730 | 14020 | 15140 | 16100 |
| 5 HT | 5030 | 5920 | 6820 | 7590 | 8500 | 9270 | 10160 | 11200 | 12090 | 12860 |

Printed on 5/12/2024 10:44 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..