

## AW 702 IND - Tekniska specifikationer



### Description

AW 702 IND har utvecklats för industriella tillämpningar för släpvagnar. Detta däck för tunga tillämpningar har utformats av BKT för att ge en ny hållbarhetsnivå.

### UM

US Standard

### Construction

 BIAS

### Machinery

Industri: Släpvagn

Version	INDUSTRIAL
Type	TT
Tyre Size	6.00 - 16
LI/SS FREE ROLLING	103 A8

## Dimensions US Standard

Usa code	94054206
Ply Rating	8
Section Width (inch)	6.7
Overall Diameter (inch)	28.4
Static Loaded Radius (inch)	13.3
Rolling Circumference (inch)	84.6
Rim Rec	4.00 E
Rim Alt	4.50 E ; 4½ K
ECE	E11-106R-004358

## Load capacity (lbs)

mph / psi	58
5 FR	2700
15 FR	2290
20 FR	2160
25 FR	1930

Printed on 5/10/2024 11:23 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..