

GF 304 - Tekniska specifikationer



Description

GF 304 är lämpligt för användning på golfbanor med golfbilar. GF 304 ger maximal komfort och skydd till banan. GF 304 finns även i en version "med stålbälte" som ger extra hög motståndskraft mot punkteringar.

UM

International Standard

Construction

 BIAS

Machinery

Lantbruk: Golfbil

Version	ARAMID BELTED
Type	TL
Tyre Size	18 X 8.50 - 8

Dimensions International Standard

Ply Rating	4
Section Width (mm)	216
Overall Diameter (mm)	460
Static Loaded Radius (mm)	202
Rolling Circumference (mm)	1334
Rim Rec	7.00 I - 55 ; I - 70 ; I - 90
ECE	E11-106R-005218

Load capacity (Kg)

km/h / bar	1.50
15	375

Printed on 5/18/2024 12:41 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..