

## COMMANDER 3 RIB - Teknik Özellikler



### Description

COMMANDER 3 RIB, toprak işleme ve taşıma operasyonları için tasarlanmış, önde 3 kuşaklı desene sahip bir ön lastiktir. Orta kuşaklarda ve omuz kuşaklarında optimize edilmiş ağırlık dağılımı sayesinde mükemmel dayanıklılık ve yük kapasitesi sağlar. Güçlü gövde, kesilme ve kopmaya karşı dirençli hamur ile birlikte olağanüstü delinme direnci sağlar.

### UM

International Standard

### Construction

 BIAS

### Machinery

Zirai: Tek çeker traktör

Version	STANDARD
Type	TT
Tyre Size	6.00 - 16
LI/SS	94 A6

## Dimensions International Standard

Ply Rating	8
Section Width (mm)	175
Overall Diameter (mm)	740
Rim Rec	4.50 E
Rim Alt	4.00 E ; 5.00 F
ECE	E11-106R-004415
TRA Code	F2

## Load capacity (Kg)

km/h / bar	4.50
30	670

Printed on 5/18/2024 1:21 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..