

FL 635 - Teknik Özellikler

Description

FL 635, hem yol hem de arazi kullanımı için uygun bir radyal yayılma lastiğidir. Özel blok diş deseni, saman balyalama uygulamaları için tasarlanmıştır. FL 635, taban izi boyunca zeminde mükemmel bir basınç dağılımı sağlar ve ekinlerin değerini korumak için toprak sıkışmasını büyük ölçüde azaltır. Lastik, mükemmel hız özellikleriyle birlikte harika kendi kendini temizleme özellikleri, dayanıklılık ve çekiş sağlar.



UM

US Standard

Construction

 RADIAL

Machinery

Zirai: Balya makinesi

Version	STANDARD
Type	TL
Tyre Size	500/45 R 22.5
LI/SS	136 D

Dimensions US Standard

Usa code	94075607
Section Width (inch)	19.3
Overall Diameter (inch)	40.2
Static Loaded Radius (inch)	18.1
Rolling Circumference (inch)	121.5
Rim Rec	AG 16.00
ECE	E11-106R-0010082

Load capacity (lbs)

mph / psi	17	23	29	35	41
45	2480	3020	3430	3970	4500
40	2720	3320	3760	4350	4940
30	3300	4010	4550	5270	5990
25	3700	4510	5110	5920	6720
20	4110	5000	5680	6570	7460
15	4300	5240	5940	6880	7800
5	4890	5960	6770	7840	8900

Printed on 5/9/2024 4:37 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..