

AW 09 - Technical Specifications



Description

AW 09 has been developed for soil tillage, hay harvesting and transport applications with implements, balers and trailers. It is ideal for modern farming both on and off the road. Its reinforced carcass ensures high load capacity and a longer service tire life. AW 09 has been designed with a special cut-and-chip-resistant compound that provides extraordinary stubble resistance.

UM

US Standard

Construction

 BIAS

Machinery

Agriculture: Baler • Hay Harvester • Implement Machinery
• Trailer

Version	STANDARD
Type	TL
Tyre Size	300/80 - 15.3
LI/SS DRIVE WHEEL	126 A8
LI/SS FREE ROLLING	138 A8

Dimensions US Standard

Usa code	94037902
Section Width (inch)	11.6
Overall Diameter (inch)	33.9
Static Loaded Radius (inch)	14.8
Rolling Circumference (inch)	99.2
Rim Rec	9.00
ECE	E4-106R-000377

Load capacity (lbs)

mph / psi	52
5 FR	7290
15 FR	6190
20 FR	5830
25 FR	5200
5 DW	5250
15	4460
20 DW	4200
25 DW	3750

Printed on 4/28/2024 10:37 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..