

## FL 630 SUPER - Technical Specifications



### Description

FL 630 SUPER is a flotation tire suitable for field and road applications with trailers, tankers and spreaders. Its resistant structure provides excellent traction and perfect grip even in bends and when maneuvering, while a reinforced bead and steel belts ensure enhanced durability.

### UM

International Standard

### Construction



RADIAL

### Machinery

Agriculture: Spreader • Tanker • Trailer

Version	STANDARD
Type	TL
Tyre Size	600/55 R 26.5
LI/SS	165 D

# Dimensions International Standard

Section Width (mm)	611
Overall Diameter (mm)	1333
Static Loaded Radius (mm)	606
Rolling Circumference (mm)	4078
SRI (mm)	625
Rim Rec	AG 20.00
ECE	E4-106R-001414

## Load capacity (Kg)

km/h / bar	0.8	1.0	1.2	1.6	2.0	2.4	2.8	3.2	3.6	4.0
70	1505	1740	1970	2395	2770	3190	3615	3895	4315	4690
65	1650	1910	2165	2630	3040	3505	3970	4275	4740	5150
50	2000	2310	2620	3180	3680	4240	4805	5180	5740	6235
40	2245	2595	2945	3575	4135	4765	5395	5815	6445	7005
25	2605	3015	3420	4155	4805	5540	6270	6760	7490	8140
10	2970	3435	3895	4730	5470	6305	7140	7695	8530	9270

Printed on 4/27/2024 1:34 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..