

FL 630 SUPER - Technical Specifications



Description

FL 630 SUPER is a flotation tire suitable for field and road applications with trailers, tankers and spreaders. Its resistant structure provides excellent traction and perfect grip even in bends and when maneuvering, while a reinforced bead and steel belts ensure enhanced durability.

UM

International Standard

Construction



RADIAL

Machinery

Agriculture: Spreader • Tanker • Trailer

Version	STANDARD
Type	TL
Tyre Size	650/65 R 26.5
LI/SS	174 D

Dimensions International Standard

Section Width (mm)	645
Overall Diameter (mm)	1519
Static Loaded Radius (mm)	684
Rolling Circumference (mm)	4653
SRI (mm)	725
Rim Rec	AG 20.00
ECE	E4-106R-001651

Load capacity (Kg)

km/h / bar	0.8	1.0	1.2	1.6	2.0	2.4	2.8	3.2	3.6	4.0
70	1955	2260	2565	3115	3600	4150	4700	5065	5615	6100
65	2145	2480	2815	3420	3955	4560	5160	5565	6165	6700
50	2600	3005	3410	4140	4785	5515	6245	6735	7465	8110
40	2920	3375	3830	4650	5380	6200	7020	7570	8390	9115
25	3390	3920	4450	5405	6250	7205	8155	8790	9745	10590
10	3860	4465	5070	6155	7120	8205	9290	10010	11100	12060

Printed on 4/27/2024 3:04 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..