

RIDEMAX FL 693 M - Technical Specifications



Description

RIDEMAX FL 693 M is the ideal radial tire for those who frequently travel on the road with trailers/tank trucks. Actually designed for 75% on-the-road use, RIDEMAX FL 693 M provides excellent road performance prioritizing both comfort and self-cleaning properties. The speed index classes D/E of the range stands for higher speeds when travelling on the road leading to significant time savings. The low rolling resistance contributes to less fuel consumption, while a reinforced bead and steel belts ensure enhanced durability.

UM

US Standard

Construction

 RADIAL

Machinery

Agriculture: Tanker • Trailer

Version	STANDARD
Type	TL
Tyre Size	710/50 R 30.5
LI/SS	173 D

Dimensions US Standard

Usa code	94037049
Section Width (inch)	28.6
Overall Diameter (inch)	58.5
Static Loaded Radius (inch)	26.6
Rolling Circumference (inch)	178.5
Rim Rec	AG 24.00
Rim Alt	AG 20.00
ECE	E4-106R-001498

Load capacity (lbs)

mph / psi	15	17	23	29	35	41	46	52	58
45	4890	5560	6750	7800	8990	10180	10980	12170	13230
40	5300	6020	7310	8450	9740	11030	11890	13180	14330
30	6430	7290	8850	10240	11790	13360	14400	15960	17340
25	7220	8190	9940	11510	13260	15010	16180	17930	19490
15	8390	9510	11550	13360	15400	17440	18790	20830	22640
5	9550	10840	13160	15220	17550	19860	21420	23730	25790

Printed on 4/20/2024 11:15 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..