

AGRIMAX RT 600 - Technical Specifications

Description

AGRIMAX RT 600 is the ideal tire for grassland, harvesting and spreading applications. Thanks to its large contact area, AGRIMAX RT 600 ensures an excellent pressure distribution on the land reducing damage on grassland and protecting your soil. Thanks to its round shoulder technology, the reinforced bead and increased number of lugs, it guarantees great stability and traction.

UM

US Standard

Construction

 RADIAL

Machinery

Agriculture: Harvester • Spreader • Tractor



Version	STEEL BELTED
Type	TL
Tyre Size	IF 710/75 R 34 CFO
LI/SS	184A8/B

Dimensions US Standard

Usa code	94512317
Section Width (inch)	28.1
Overall Diameter (inch)	75.6
Static Loaded Radius (inch)	33.7
Rolling Circumference (inch)	227.2
Rim Rec	DW25 B
Rim Alt	DW23 B
ECE	E11-106R-0010577

Load capacity (lbs)

mph / psi	9	12	15	17	20	23	29	35	41	46
30	7740	9130	10520	11710	13090	14290	15670	16860	18450	19840
25	7740	9130	10520	11710	13090	14290	15670	16860	18450	19840
10	8910	10500	12100	13470	15070	16430	18030	19400	21230	22820
5	9830	11600	13360	14870	16630	18140	19910	21430	23430	25200
Upto 20 Cyc	10060	11870	13680	15220	17030	18570	20380	21920	24000	25790
Upto 10 Cyc	12000	14150	16300	18150	20300	22140	24300	26150	28600	30750
Upto 5 Cyc	13160	15520	17880	19910	22270	24290	26650	28670	31370	33730

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 5/1/2025 2:21 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..