

AGRIMAX RT 657 - Technical Specifications



Description

AGRIMAX RT 657 is the ideal tire for on-the-road usage and soil tillage; some sizes are also suitable for vineyard harvesting. This tire guarantees excellent driving comfort as well as significant fuel savings. It has a high load capacity also at high speed levels. AGRIMAX RT 657 is the best choice for those who need a versatile and reliable tire, with no compromise on performance.

UM

International Standard

Construction

 RADIAL

Machinery

Agriculture: Tractor • Vineyard Harvester

Version	SPECIAL
Type	TL
Tyre Size	600/65 R 38
LI/SS	159 D/162 A8

Dimensions International Standard

Section Width (mm)	611
Overall Diameter (mm)	1745
Static Loaded Radius (mm)	790
Rolling Circumference (mm)	5247
SRI (mm)	825
Rim Rec	DW 20 B
Rim Alt	W 18 L
ECE	E4-106R-000623
TRA Code	R1W

Load capacity (Kg)

km/h / bar	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4
65	2100	2450	2760	3065	3370	3635	4025	4375
50	2210	2575	2895	3220	3540	3815	4230	4595
40	2280	2660	2995	3325	3660	3945	4370	4750
30	2420	2820	3175	3525	3880	4180	4635	5035
10 LT	2820	3285	3695	4110	4520	4870	5400	5865
10 HT	2420	2820	3175	3525	3880	4180	4635	5035

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 5/3/2025 12:08 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..