

AGRIMAX RT 765M - Technical Specifications



Description

AGRIMAX RT 765M, a BKT 70 series tire, is suitable for cutting-edge tractors for several heavy-duty applications such as soil tillage, field and road transport, vineyard harvesting, and spraying. A wide contact patch ensures the best possible traction and comfort on all surfaces at any time. This tire provides great self-cleaning properties and reduced soil compaction. Two sizes are available with steel-belted technology.

UM

International Standard

Construction

 RADIAL

Machinery

Agriculture: Sprayer • Tractor • Vineyard Harvester

Version	SPECIAL
Type	TL
Tyre Size	710/70 R 42
LI/SS	173D/176A8

Dimensions International Standard

Section Width (mm)	716
Overall Diameter (mm)	2061
Static Loaded Radius (mm)	922
Rolling Circumference (mm)	6174
SRI (mm)	975
Rim Rec	DW 23 B
Rim Alt	DW 25 B
ECE	E11-106R-006018
TRA Code	R1W

Load capacity (Kg)

km/h / bar	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4
65	3120	3640	4095	4550	5005	5395	5980	6500
50	3280	3825	4300	4780	5260	5665	6280	6825
40	3410	3980	4475	4970	5470	5895	6535	7100
30	3590	4190	4710	5235	5760	6205	6880	7475
10 LT	4185	4880	5490	6100	6710	7230	8015	8710
10 HT	3590	4190	4710	5235	5760	6205	6880	7475

Printed on 5/30/2023 3:50 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..