

AGRIMAX RT 765 - Technical Specifications



Description

AGRIMAX RT 765, a BKT 70 series tire, is suitable for cutting-edge tractors for several heavy-duty applications such as soil tillage, field and road transport, vineyard harvesting, and spraying. A wide contact patch ensures the best possible traction and comfort on all surfaces at any time. This tire provides great self-cleaning properties and reduced soil compaction. Two sizes are available with steel-belted technology.

UM

US Standard

Construction

 RADIAL

Machinery

Agriculture: Sprayer • Tractor • Vineyard Harvester

Version	STANDARD
Type	TL
Tyre Size	650/75 R 42
LI/SS	170 D

Dimensions US Standard

Usa code	94065493
Section Width (inch)	25.8
Overall Diameter (inch)	80.4
Static Loaded Radius (inch)	36.1
Rolling Circumference (inch)	242
Rim Rec	DW21B
Rim Alt	DW20B;DW23B
ECE	E11-106R-006402
TRA Code	R1W

Load capacity (lbs)

mph / psi	9	12	15	17	20	23	29	35
40	6220	7140	8200	9260	10320	11380	12430	13230
30	6540	7510	8620	9720	10840	11950	13060	13890
25	6810	7830	8980	10140	11300	12470	13620	14480
15	7150	8220	9440	10650	11870	13080	14310	15210
5 LT	8330	9580	10990	12410	13830	15240	16670	17720
5 HT	7150	8220	9440	10650	11870	13080	14310	15210

Printed on 4/29/2024 9:26 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..