

## AGRIMAX RT 855 - Technical Specifications



### Description

AGRIMAX RT 855 provides excellent traction and comfort properties. Mainly designed for soil tillage and both field and road transport, some sizes are also suitable for spraying, and vineyard harvesting. AGRIMAX RT 855 has excellent self-cleaning features that allow for a quick change from field operations to road usage.

### UM

US Standard

### Construction

 RADIAL

### Machinery

Agriculture: Sprayer • Tractor • Vineyard Harvester

Version	STANDARD
Type	TL
Tyre Size	250/85 R 20 (9.5 R 20)
LI/SS	116 A8/B

Dimensions US Standard

Usa code	94027460
Section Width (inch)	9.8
Overall Diameter (inch)	37
Static Loaded Radius (inch)	16.7
Rolling Circumference (inch)	110.7
Rim Rec	W 8
Rim Alt	W 7 ; W 9
ECE	E4-106R-000639
TRA Code	R1W

Load capacity (lbs)

mph / psi	9	12	15	17	20	23	29	35
30	1300	1490	1710	1930	2150	2370	2570	2760
25	1300	1490	1710	1930	2150	2370	2570	2760
20	1390	1600	1840	2070	2310	2550	2760	2950
5 LT	1740	2000	2290	2590	2890	3190	3440	3690
5 HT	1390	1600	1840	2070	2310	2550	2760	2950

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 5/1/2025 3:48 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..