

## AGRIMAX RT 855 - Technical Specifications



### Description

AGRIMAX RT 855 provides excellent traction and comfort properties. Mainly designed for soil tillage and both field and road transport, some sizes are also suitable for spraying, and vineyard harvesting. AGRIMAX RT 855 has excellent self-cleaning features that allow for a quick change from field operations to road usage.

### UM

International Standard

### Construction



RADIAL

### Machinery

Agriculture: Sprayer • Tractor • Vineyard Harvester

Version	STANDARD
Type	TL
Tyre Size	320/85 R 36
LI/SS	147 D/150 A8

# Dimensions International Standard

Section Width (mm)	329
Overall Diameter (mm)	1458
Static Loaded Radius (mm)	672
Rolling Circumference (mm)	4404
SRI (mm)	700
Rim Rec	W 11
Rim Alt	W 9 ; W 10
ECE	E11-106R-003511
TRA Code	R1W

## Load capacity (Kg)

km/h / bar	0.8	1.0	1.2	1.6	2.0	2.4	2.8	3.2	3.6	4.0	4.4
65	1160	1330	1500	1810	2010	2120	2320	2515	2685	2825	3075
50	1220	1400	1575	1905	2110	2230	2440	2645	2825	2970	3230
40	1270	1455	1645	1985	2200	2325	2540	2755	2945	3095	3350
30	1335	1530	1725	2080	2310	2440	2665	2895	3090	3250	3540
10 LT	1555	1785	2010	2430	2695	2845	3110	3375	3605	3790	4125
10 HT	1335	1530	1725	2080	2310	2440	2665	2895	3090	3250	3540

Printed on 5/8/2024 5:30 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..