

## AGRIMAX RT 855 - Technical Specifications



### Description

AGRIMAX RT 855 provides excellent traction and comfort properties. Mainly designed for soil tillage and both field and road transport, some sizes are also suitable for spraying, and vineyard harvesting. AGRIMAX RT 855 has excellent self-cleaning features that allow for a quick change from field operations to road usage.

### UM

International Standard

### Construction

 RADIAL

### Machinery

Agriculture: Sprayer • Tractor • Vineyard Harvester

Version	STANDARD
Type	TL
Tyre Size	340/85 R 36 (13.6 R 36)
LI/SS	132 A8/B

## Dimensions International Standard

Section Width (mm)	353
Overall Diameter (mm)	1492
Static Loaded Radius (mm)	689
Rolling Circumference (mm)	4507
SRI (mm)	725
Rim Rec	W 12
Rim Alt	W 11
ECE	E4-106R-000763
TRA Code	R1W

## Load capacity (Kg)

km/h / bar	0.6	0.8	1.0	1.2	1.4	1.6
50	1100	1280	1460	1640	1820	2000
40	1100	1280	1460	1640	1820	2000
30	1180	1370	1565	1755	1950	2140
10 LT	1475	1720	1960	2200	2440	2680
10 HT	1180	1370	1565	1755	1950	2140

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 5/1/2025 3:40 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..