

AGRIMAX RT 855 - Technical Specifications



Description

AGRIMAX RT 855 provides excellent traction and comfort properties. Mainly designed for soil tillage and both field and road transport, some sizes are also suitable for spraying, and vineyard harvesting. AGRIMAX RT 855 has excellent self-cleaning features that allow for a quick change from field operations to road usage.

UM

US Standard

Construction

 RADIAL

Machinery

Agriculture: Sprayer • Tractor • Vineyard Harvester

Version	STANDARD
Type	TL
Tyre Size	420/80 R 46 (16.9 R 46)
LI/SS	151 D/162 A2

Dimensions US Standard

Usa code	94046089
Section Width (inch)	16.5
Overall Diameter (inch)	72.4
Static Loaded Radius (inch)	34
Rolling Circumference (inch)	222.1
Rim Rec	W 13
Rim Alt	W 12
ECE	E4-106R-001730
TRA Code	R1W

Load capacity (lbs)

mph / psi	9	12	15	17	20	23	29	35
40	3580	4110	4720	5320	5940	6550	7080	7610
30	3760	4320	4960	5600	6240	6880	7440	7990
25	3920	4510	5170	5840	6500	7180	7760	8330
20	4120	4730	5430	6130	6830	7530	8150	8750
5	4930	5650	6490	7330	8170	9010	9740	10470
5 LT	4790	5510	6330	7140	7960	8770	9490	10200
5 HT	4120	4730	5430	6130	6830	7530	8150	8750

Printed on 5/9/2024 1:38 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..