

AGRIMAX RT 855 - Technical Specifications



Description

AGRIMAX RT 855 provides excellent traction and comfort properties. Mainly designed for soil tillage and both field and road transport, some sizes are also suitable for spraying, and vineyard harvesting. AGRIMAX RT 855 has excellent self-cleaning features that allow for a quick change from field operations to road usage.

UM

International Standard

Construction



RADIAL

Machinery

Agriculture: Sprayer • Tractor • Vineyard Harvester

Version	STANDARD
Type	TL
Tyre Size	520/85 R 46 (20.8 R 46)
LI/SS	158 A8/B

Dimensions International Standard

Section Width (mm)	516
Overall Diameter (mm)	2052
Static Loaded Radius (mm)	930
Rolling Circumference (mm)	6157
SRI (mm)	975
Rim Rec	DW 16 L ; W 16 A ; W 16 L ; DD 16
Rim Alt	DW 18 L ; W 18 L ; W 18 A
ECE	E4-106R-001415
TRA Code	R1W

Load capacity (Kg)

km/h / bar	0.6	0.8	1.0	1.2	1.4	1.6
50	2340	2720	3105	3485	3870	4250
40	2340	2720	3105	3485	3870	4250
30	2505	2915	3325	3735	4145	4550
10 LT	3135	3645	4160	4670	5185	5695
10 HT	2505	2915	3325	3735	4145	4550

Printed on 5/8/2024 10:29 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..