

AGRIMAX RT 945 - Technical Specifications



Description

AGRIMAX RT 945 is specially designed for row crops: it does not damage the crops and preserves the yield. Excellent self-cleaning features allow for a quick change from field operations to road usage, where AGRIMAX RT 945 shows brilliant performance. Its strong carcass gives the tire excellent stability, outstanding traction, and exceptional durability.

UM

US Standard

Construction

 RADIAL

Machinery

Agriculture: Sprayer • Tractor

Version	STANDARD
Type	TL
Tyre Size	380/90 R 46 (14.9 R 46)
LI/SS	159 A8/B

Dimensions US Standard

Usa code	94021833
Section Width (inch)	15
Overall Diameter (inch)	72.9
Static Loaded Radius (inch)	33.8
Rolling Circumference (inch)	224.4
Rim Rec	W 12
Rim Alt	W 11 ; W 13
ECE	E4-106R-001409
TRA Code	R1W

Load capacity (lbs)

mph / psi	12	17	23	29	35	41	46	52	58	64
30	3940	5050	6150	6760	7260	7950	8540	8970	9640	-
25	3940	5050	6150	6760	7260	7950	8540	8970	9640	-
20	4210	5400	6590	7230	7780	8510	9150	9610	10330	-
5	4620	6030	7310	8720	10010	10390	11540	12820	13320	14470

Printed on 4/23/2024 7:45 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..