

AGRIMAX RT 945 - Technical Specifications



Description

AGRIMAX RT 945 is specially designed for row crops: it does not damage the crops and preserves the yield. Excellent self-cleaning features allow for a quick change from field operations to road usage, where AGRIMAX RT 945 shows brilliant performance. Its strong carcass gives the tire excellent stability, outstanding traction, and exceptional durability.

UM

US Standard

Construction

 RADIAL

Machinery

Agriculture: Sprayer • Tractor

Version	STANDARD
Type	TL
Tyre Size	380/90 R 54 (14.9 R 54)
LI/SS	158 A8/B

Dimensions US Standard

Usa code	94046799
Section Width (inch)	15
Overall Diameter (inch)	80.9
Static Loaded Radius (inch)	37.9
Rolling Circumference (inch)	245.4
Rim Rec	W 12
Rim Alt	W 11 ; W 13
ECE	E4-106R-001488
TRA Code	R1W

Load capacity (lbs)

mph / psi	12	17	23	29	35	41	46	52
30	4310	5530	6750	7310	7970	8720	9370	-
25	4310	5530	6750	7310	7970	8720	9370	-
20	4620	5920	7230	7830	8530	9340	10030	-
5	5060	6610	8010	9560	10970	11390	12650	14050

Printed on 4/20/2024 6:07 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..